

WCIS SnoXcross Rules

35 Adrian Road, P.O. Box 203, Perry, NY 14530

Track (585) 237-2510 - Office (585) 237-2580

<http://www.wyomingcountyinternationalspeedway.com/rules.htm>

2005 – 2006 RULES & REGULATIONS

Safety First

Competitor and spectator safety is the overriding priority at all of our events. Your machine and your personal safety equipment will be safety inspected before you compete for the first time.

Your snowmobile must be equipped with the following:

A tether cord kill switch, as well as, a thumb activated shut off switch. The switch must be located on the right hand side of your handlebars.

Head lights and tail lights must be operational and must be covered with clear tape.

The Ski tips or loops on your skis must be a minimum of 1" inch in diameter or width.

Ski loops must loop around and attach under the front Ski tip.

Your sled must also be equipped with an extended rear snow flap, that touches the ground when the racer is on the sled.

Warm up stands must be of solid construction and must be designed to contain debris that may be thrown off the snowmobile track during warm up procedure. Warm up stands must have a complete enclosure panel with side deflectors.

RACER SAFETY REQUIREMENTS

Racers must wear a Snell 2000 or newer approved Full coverage helmet with eye protection.

25% of your helmet must be bright orange in colour. Helmets must have the original Snell 2000 or newer approved label on it to pass safety inspection.

You will also need gloves, good quality boots, hockey type shin and knee pads.

All racers are required to wear an approved upper body vest that provides full chest and back protection. Motocross Vests are not legal for Snowcross racing.

TRACTION PRODUCTS & CARBIDES

Studs: You are permitted to use a maximum of (96) studs in your track at Snowcross races. The studs and backer plates must be located in the centre area between the slide rails. Studs and backer plates are not permitted under the slide rails or on the outside ribs of the track.

Studs must be located no more than 1.25" inches directly behind a track lug and a minimum of 3.75" inches from the outside edge of the track. Track studs must not be more than 3/8" taller than the track lug located directly in front of the stud. Studs must be commercially available, trail type studs with a minimum 60% angled tip. Studs and backing plates can not be sharpened or modified at any time.

Ski Runners: Carbide runners must be commercially available 60% or 90% trail type carbides with a host bar that has rounded edges. Maximum carbide cutting edge insert length is 10" inches. Carbides can not be sharpened at any time. Oval or Ice racing carbides are not permitted. The minimum width for a carbide runner is 3/8" inch. Maximum width 5/8" inch. The maximum height for the carbide runner from the bottom of the ski is a maximum of 1/8" higher than the width of the carbide runner. Not to exceed 5/8" inch.

Example #1: If your carbide runner is 3/8" inch wide, the maximum total height for your carbide runner including carbide insert is 1/2" inch from the bottom of the ski surface..

Example #2: If your carbide runner is ½" inch wide, the maximum total height for your carbide runner including carbide insert is 5/8" inch from the bottom of the ski surface.

Competitors can not modify or remove or change any part of your snowmobile in any Stock racing classes unless it is written or approved by WCIS (Racers are responsible to know all WCIS General rules and Snowcross rules).

COMPETITOR RACING NUMBERS

All racers must use 6" or 7 " black racing numbers on white back grounds. (All classes).

Racer numbers must be located on both sides of the snowmobile and must not be obstructed while you are racing.

Race number #1 is reserved for the 2004 National Champion.

Two digit numbers are reserved for Pros and Semi-Pros only. All other new racers must choose a three digit number between 100 - 999.

Note:

No express or implied warranty or safety will result from publication of or compliance with these rules and regulations. They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to spectators or participants.

These regulations are comprised of definitions and allowable modification or alterations.

If a definition, modification or alteration is not cited then it is to be construed that no modification, alteration or change can be made to the component unless it is specifically approved by the rules committee. Existing rules may be revised, or new rules may be added after this rulebook.

The WCIS rulebook is designed as a guideline or quick reference tool to help you understand the rules that pertain to Snocross racing.

All racers should be fully aware of the regulations set out in the WCIS rule book and should be prepared to abide by them.

The regulations are compromised of definitions and allowable modifications or alterations.

If a definition, modification or alteration is not cited then it is to be construed that no modification, alteration or change can be made to the component unless it is specifically approved and published by the WCIS rules committee.

It is a racer's responsibility to present a snowmobile that is legal at all times. It is not WCIS responsibility to detect every rules violation at every inspection.

If you have any further questions concerning rules, please contact our Technical Director

This rulebook went to print AUG 31, 2005. All rules in this rulebook are subject to change. Please check back for rule changes, additions and information not included in this rulebook. It is the driver's responsibility to visit our website prior to each race to make sure they have the latest updates. WCIS reserves the right to change or modify these rules at any time.

DRIVERS UNDER 18 YEARS OF AGE [Introduction]

1. Drivers under the age of eighteen (18) are required to have an original notarized Minor Waiver on file at WCIS Inspection Headquarters before they will be allowed to compete.
2. Drivers under the age of eighteen (18) are required to sign the Minor's Assumption of Risk Acknowledgement at driver check in at each event. No Exceptions!
3. Drivers under the age of eighteen (18) must have a parent or legal guardian with them at driver check-in. If a parent or legal guardian is not able to attend driver check in, an original notarized Power of Attorney form must be presented with proper ID at driver check-in. Please contact WCIS headquarters for this form.

4. Any driver or parent caught falsifying a driver's age or producing false documents will be suspended for the remainder of the season.

CLASSES

Stock - Modified - Open Class - Juniors - 120's

RACE DIRECTOR AUTHORITY

1. The Race Director shall be responsible for the conduct of the race. He shall have the right to make the final determination concerning all aspects of the race and the race facility, including design. Any and all of these rules and regulations are not withstanding.
2. The Race Director shall have the voice of authority to discipline the participants for violation of the rules. Such discipline will be limited to disqualification of a participant and/or exclusion from an event.
3. Disciplinary action by the Race Director other than a disqualification or prescribed fines will be under provisions of the Board.
4. The Race Director and Technical Director will be certified by the sanctioning organization.
5. Official race results shall be approved by the assigned Race Director and a signed copy will be returned to the promoter for announcement and distribution.
6. The Technical Director shall carry and be responsible for the official specifications and certain instruments for measurements concerning verification and control of contestant's machines.
7. The Race Director may cancel any race or the entire event for reasons of safety regarding competitors or spectators, and in such case shall determine the awards, if any. The Race Director may shorten the race for any reasons of safety but must give drivers adequate notice in advance.
8. A Race Director may judge the mechanical integrity of all timing equipment.
9. The number of competitors that can be safely on the course at any one time will be determined by the Race Director.

NOTES

FLAG DEFINITIONS

All drivers **MUST** pay close attention to the flags as they will be displayed throughout the entire race.

GREEN FLAG

The green flag is lifted to start the race. The course is clear and race is in progress.

YELLOW FLAG

NO PASSING is allowed in any yellow flag zone (the area from the yellow flag to the end of the incident). A yellow flag means there is an incident ahead and there may be some track blockage. All drivers will slow down, observe the caution, and most importantly, NOT PASS until clear of the incident and through the yellow flag zone. All sleds must "roll" over the terrain in a yellow flag area. PASSING under a yellow flag will not be tolerated.

JUMPING UNDER A YELLOW FLAG

Jumping under yellow constitutes a safety hazard. Any rider caught jumping under yellow will receive a DQ and 20 points for that heat. If it happens in a final, the rider will receive 0 points. In a situation where the yellow flag is displayed for numerous laps, riders must obey the yellow flag for all of those laps. If the yellow is waving in conjunction with a checkered flag, the riders must still obey the yellow and "roll over" the finish line jump.

PASSING UNDER A YELLOW FLAG

A pass under a yellow flag will result in a black flag and the rider will be motioned to the back of the field. Should this not be possible due to communication difficulties or any other reason, that rider will be scored last in his heat or final.

RED FLAG

The race will stop immediately, regardless of your position on the track. Slow down and stop with caution as the drivers behind you may not have seen the red flag. The restart position of the drivers reverts back to the last officially counted lap. If only one (1) lap or less has been completed, the restart will be the same as the start of the race. No work may be performed on the machines without permission from a race official. Raising the hood will be considered a violation of this rule and the offending driver will be lined up at the rear of the field.

BLACK FLAG

A furled black flag (the black flag is wrapped around the stick) signifies a warning for either equipment failure or for driver conduct. A furled black flag pointed at you is a warning to stop whatever activity has caught the eye

of the officials. Should you not cease the offending activity, you WILL promptly be displayed an open black flag. An important note regarding an open black flag – the display of this flag is NOT an immediate disqualification. It is a penalty flag and might only require a stop-and-go penalty or the like. DO NOT simply leave the track if you receive an open black flag.

Instead you should continue your lap, then carefully slow down and stop at the start/finish line. Keep your eyes on the head flagman as he may simply slow you down until, for instance, the competitor you passed in a yellow zone, or passed with too much contact, goes by. He will then wave you back up to speed. The penalty, if the infraction is judged to be more serious, may be a "stop-and-go." Always, of course, rejoin the action in a safe, observant manner. Only in the most extreme cases, the flagman may hold you until the entire field has passed (i.e. for cutting the course) or may inform you that you have been disqualified. In that event, exit the racecourse safely and report back to your paddock or staging area.

In the event that you disagree with the decision of the officials regarding a black flag penalty, please be advised that all such calls will be made solely at the discretion of the Race Director, after any and all necessary information has been gathered. Should you disagree, regardless of how strongly you disagree, you may present your case directly, and ONLY, to the Race Director, and in an appropriate manner. You must NOT engage or accost any trackside official with any abusive volume or language. To do so may be grounds for IMMEDIATE DISQUALIFICATION. This is a professional series, and we expect ALL involved to act accordingly. Your argument, when presented in an appropriate manner, will be duly considered and, should your protest have merit, the decision of the officials could be reviewed.

DISQUALIFICATION UNDER A BLACK FLAG

Regardless of the situation, all attempts will be made to notify a rider in competition of a black flag. Should it not be possible, for what ever reason, the rider will be informed as soon as possible after the race.

BLUE FLAG

The blue flag will be displayed to machines being lapped.

WHITE FLAG

The white flag will be displayed when drivers have started their last lap.

CHECKERED FLAG

The race is complete. Should a checkered flag be displayed later than the official distance, the finishing order will be decided on the basis of the official distance. ALL sleds are to proceed immediately to the tech area. You may be required to stop for a post race technical inspection unless otherwise instructed by an official.

CREW & DRIVER REGULATIONS

All drivers and crew who enter secured areas within the facility must be aware of and abide by these rules and all applicable rules in the general competition section. The intent of these rules is to establish a venue in which all qualified drivers and machines can compete at their own level. These rules are definitions and guidelines which allow for modifications or alterations. If a definition, modification or alteration is not cited, then it is to be construed that no modification, alteration or change can be made to the component unless it is specifically approved by the rules committee.

DRIVER & MACHINE [General Regulations]

1. A driver and the machine's chassis and motor shall be considered a unit and once the class has begun, neither will be substituted. If a driver has qualified on a machine, both the driver and the chassis and motor must be in the same final event of the class. Any driver caught substituting a chassis or motor will be subject to immediate disqualification and possible disciplinary action and may lose all points at the event in that class.

RACE REGISTRATION & ENTRY REGULATIONS

1. A signed Released and Waiver of Liability, Assumption of Risk and Indemnity Agreement form is mandatory for all personnel in non-spectator areas (paddock, staging and track) at each event.
2. All drivers must have registered at race headquarters and have signed a Released and Waiver of Liability, Assumption of Risk and Indemnity Agreement before any runs are made (practice or racing). Any driver caught practicing or racing without proper waiver and registration forms filled out may be disqualified. All entries must be to the appropriate WCIS office by the proper deadline.

This does not guarantee your entry in the race - some classes will be full before this date.

3. Please check with your racing circuit for their refund policy of entry fees.
4. Please check with your racing circuit for their refund policy of additional fees.
5. Regional service fees or insurance fees are not considered part of entry fees.
6. Gate admission fees for driver and crew members will be regulated on a regional basis.
7. Each affiliate will provide an order of events.
8. The maximum number of classes a driver can enter per day will be regulated on a regional basis. Driver and machine may race other higher classes in the same division.
9. Any class or event can be eliminated when there are less than three (3) official entries at the close of registration.
10. All participants in events must be fully familiar with the Rules and Regulations, and any additional rules by Race Promoters that may be specifically applied to any event.
11. All participants are responsible for at least a 10 BC fire extinguisher in their pit area.
12. All drivers are responsible for the proper disposal of hazardous materials (examples; gasoline, oil, antifreeze, etc.) and waste (garbage). Any driver not in compliance will receive a fine.

Gloves and appropriate clothing are mandatory.

Eye protection is mandatory. Face masks may be required at the starting line at the discretion of the Race Director. If corrective lenses are required to drive a motor vehicle, the driver will also be required to wear them while racing.

Noise silencers or hearing protection are mandatory in all modified classes.

7. The use of upper body protection equipment is mandatory. The upper body protection must cover all body areas. Motocross vests and hockey equipment do not meet this rule.
8. Shoulder pads are to be added to the upper body protection.
9. Shin and knee guards are mandatory. Shin and knee guards will be worn on both legs. The shin guard must extend from the instep to above the kneecap and be constructed of an impenetrable material.
10. Elbow pads are highly recommended in all forms of racing.

DRIVER LIABILITY

The driver, in signing the Driver Entry waiver and Release and Waiver of Liability, Assumption of Risk and Indemnity Agreement elect to use the course at the event at their own risk, and thereby releases the sanctioning organization together with their heirs, assigns, officers, representatives, agents, employees, and members, sponsoring organization and owners of properties on which sanctioned events are to be held from all liability from injury to person, property may be received by said entrant and from all claims of said injuries to the parties listed above growing out of, or caused by any construction or condition of the course over which the event is held.

DRIVER RESPONSIBILITY & PIT CREW

Members of pit crew, etc., are the responsibility of the driver to whom assigned. If a crew member lets someone else use their wristbands, tries to enter restricted areas without the proper identification, wristband or signing a waiver, or in any other way becomes a problem for WCIS race officials, the driver whom they are with, can be penalized up to and including disqualification.

MISUSE OF PIT PASSES

Improper usage of pit or paddock passes may be grounds for discipline. This disciplinary action may include fines and possible disqualification for the driver.

FRAUD, BRIBERY & ILLEGAL ASSISTANCE

In addition to non-compliance with any of the above regulations or rules, the following offenses shall be considered a breach of regulations subject to disqualification:

1. Bribing or attempting to bribe anyone connected with the race; accepting or offering to accept a bribe.
2. A competitor accepting any kind of assistance that aids in machine operation during the race.
3. Any fraudulent proceedings or act of prejudicing the interest of the race generally.

DRIVER CHECK-IN [General Regulations]

1. All drivers and crew members are required to check in, sign a Release and Waiver of Liability.

Everyone who is in the pit area must be wearing a wristband on their wrist. Drivers or their pit crew caught in the pit area without a wristband,

switching wristbands, or using old wristbands could subject the driver to disciplinary action, fines, and possible qualification.

Drivers must be checked in by the appointed time.

DRIVERS MEETING

The mandatory Driver's Meeting will be held at an announced time and place. It will be conducted by the Race Director and/or Race Promoter. Descriptions of the course, flags, etc. will be made. Pins, stamps, tags, etc. may be used to check the identity of drivers at the meeting. Drivers not attending this meeting are subject to penalties or fines (i.e. no practice).

PRACTICE LAPS

There will be an open practice session (hot laps) on each race day dependent upon snow conditions. This time may vary due to race conditions. Refer to the order of events for times. Drivers should report to the staging area to run practice laps. Length of practice sessions will be determined by amount of time available at each event by race officials. All drivers must be registered and have signed all waivers. Any driver caught on the practice track without being registered or having signed the proper waivers will be disqualified. The Race Director has the power to change or modify practice at any time.

STAGING AREA

Reasonable speeds will be observed in the pit and staging areas. Drivers will report to the staging area to run practice laps. The order of events will be posted on a board in the staging area. It is the driver's responsibility to be aware of what heat they are racing in and be in the staging area when their respective heat is called. All drivers and pit crew will be required to wear helmets and tethers while driving through pit and staging areas.

WARM-UP STANDS

1. Snowmobile stands that catch and retains traction components, and other items that are thrown by a track, are mandatory. The machine must be placed on a legally approved stand, placed within six (6) inches of the rear of the tunnel opening, and within twelve (12) inches of the track whenever the rear of a machine is raised to clean out the engine or the track. This stand is to be used whenever the rear of a machine is raised to clean out the engine or track and must be used in the paddock and pit area at all times. The stand must be constructed of a metal material sufficient to contain cleats or other items that might be thrown from a track. This material must be constructed of a metal

equivalent to 6061 T6 aluminum 1/16 inch thick. Side extensions are mandatory and at a minimum, the side extensions must extend to the center of the back axle.

2. No full throttle operation is allowed while the machine is on the warm-up stand.

TUNE-UP AREA

1. Tune-up of the engine will be performed in the proper area only when available. Drivers must consult with the Race Director to determine the proper tune-up area at each event. The tune-up area will be held on a course, completely free of obstructions, which provides adequate and safe run-off areas at the end so competitors may slow down and exit safely.

2. All driver entry fees must be paid before a driver may use the designated tune-up area.

3. All drivers and pit crew in said tune-up area must have signed the Release and Waiver of Liability, Assumption of Risk and Indemnity Agreement and be wearing the event specific wristband.

4. All appropriate safety gear and tethers are required in the tune-up area.

RACE START & START LINE

1. The driver and one (1) crew member are allowed on the start line. The driver is the ONLY person allowed in front of the machine.

2. Once the machine reaches the start line on its own power, the machine is considered to have started the race.

3. A driver may raise his hand if there is an equipment problem on the start line. The starting flagman will wait a maximum of two (2) minutes for the driver to correct the problem.

DRIVER MAY BE PENALIZED AT THE START OF A RACE FOR:

1. Jumping the start.

2. Causing a restart.

3. Unsportsmanlike conduct (at the discretion of the Race Director).

START LINE PENALTY

For classes that all of the drivers advance to the final, any driver who scores a DNS (did not start) in qualifying will be required to start from the penalty line in the final at the discretion of the Race Director. If a driver scores a DNS in all rounds of qualifying, the driver will not be allowed to compete in the final. All drivers must qualify for a final.

RACE RESTART PROCEDURE

1. The Race Director may order a restart at his discretion. The Race Director's decision is final.
2. In the event of an accident involving one (1) or more machines, the Technical Director may at his sole discretion, rule said machine(s) mechanically unsafe to participate in the restart. The machine(s) must be fully inspected and approved to be safe by the Race Director and/or the Technical Director before further competition will be permitted.
3. All machines will be stopped under the red flag. The Flagman will notify drivers when to move machines and will have them proceed slowly to the point of the restart. Any machine that is moved without permission could be subject to disqualification. Any machine causing the stop of a race and a subsequent restart, or any machine unable to immediately return to the starting line will be placed at the rear of the restart sequence.
4. The restart position of the machines reverts back to the last officially counted lap (WCIS considers a lap complete when the leader crosses the finish line). If only one (1) lap or less has been raced, the restart will be the same as the start of the race.
5. The machines involved in the restart after more than one (1) lap has been raced, will be restarted by a single file start. Drivers will be on the starting line within two (2) minutes in the case of a restart.
6. If a driver is the cause of a red flag restart, they must report immediately to the onsite ambulance and will not be allowed to restart the race that was red flagged. However, they will receive points for starting the race and will be scored last. If the start area does not allow for space for all drivers to fit side by side, the lowest qualifying drivers will be required to start from a second row at the Race Director's discretion.

PASSING

A driver must always be prepared for another machine to pass and must therefore be on the lookout for other machines approaching from behind. Drivers will not hinder or obstruct an overtaking vehicle. A slower driver is to move over for the passing machine.

LEAVING THE COURSE

1. Drivers leaving the course must re-enter in a safe fashion and without gaining a position or advantage (drivers will not be permitted to cut across the infield). Failure to follow this procedure may result in a penalty or disqualification at the discretion of the Race Director.

2. Drivers may not stop on the race course. If mechanical problems force this, the driver is responsible for getting the machine off the course.

RACE FINISH

A driver whose machine is disabled before the driver reaches the finish line may push or pull the machine, with the driver's own unaided muscular energy, across the finish line and will be considered to have completed the race. A driver is said to have finished a race when the driver is in contact and in control of the machine as it crosses the finish line.

INJURED DRIVERS & DAMAGED MACHINES

1. An injured or otherwise incapacitated driver or damaged machine shall be prohibited from racing with exception that, if in the Race Directors judgment, the driver or machine is determined not to be a danger to driver's self or any other competitor. The Race Director's decision is final.
2. If for any reason a driver is forced to stop on or near the course during an event, it would be the driver's first duty to remove the machine from the track so as not to endanger or obstruct other drivers
3. A driver who has spun out or stalled should raise both hands over their head to indicate that no more movement will be made until the field has passed and to indicate no injury.

UNSPORTSMANLIKE CONDUCT

Discipline and Violations

1. The deliberate blocking of a faster machine is cause for disqualification or a Stop and Go penalty at the discretion of the Race Director.
2. Bumping or cutting of lanes is cause for a Stop and Go penalty or disqualification at the discretion of the Race Director.
3. Any dangerous or foolish driving, crowding, chopping or unsportsmanlike conduct on the course, in the pit area, or anywhere else on the race grounds could subject contestant to disqualification at the discretion of the Race Director.

OBSTRUCTION

If for any reason a driver is forced to stop on or near the course during an event, it would be the driver's first duty to remove the machine from the track so as not to endanger or obstruct other drivers.

SIGNALS

A driver who has spun out or stalled should raise both hands over their head to indicate that no more movement will be made until the field has passed and to indicate no injury.

RADIOS

1. There will be no independent radio transmission on sanctioning bodies' radio frequencies.
2. Helmet Radios will be allowed at National events , in the PRO CLASSES ONLY. No radio communication to drivers at the Regional level.

SUPPORT VEHICLES

No unauthorized motorized vehicles are allowed in the pit or staging areas. Machines have to return under their own power. Only disabled machines may be towed from the track.

SPEEDING

Reasonable speeds will be observed in the pit and paddock area. All pit areas are caution zones where the utmost driver awareness is required.

TEMPORARY SHELTERS

No temporary construction of the following types will be permitted in the pit area. Tents forms are. enclosures are not allowed.

ANIMALS

No aggressive animals will be allowed at the race site. All animals MUST be on a leash.

PROTESTS

All formal protests must be made in writing, by a driver in the competition at the event, from the class in question, on a formal protest form accompanied by a \$100 cash protest fee.

2. Protests, grievances, etc. must be submitted within thirty (30) minutes after affected class results are posted. No protests, grievances, etc., will be accepted more than thirty (30) minutes after the posting of the results of the affected class.

3. When the official protest is made with the fee, teardown will not be complete until protest is satisfied or proven unwarranted. If the protest is valid, the fee will be returned to the protester. If a protest against another driver is made and found invalid, the fee will be given to the protested

machine owner for the inconvenience. This is to be accomplished before the machines are released from teardown.

4. There is no need for formal protests in the case of driving infractions during an event. Reports of such alleged infractions should be made to the Race Director, who in turn will request a report from the flagman or the assigned official on the course.
5. A protest must be valid in the eyes of the Race Director, or he has the option not to accept it for action.
6. No protests will be accepted that refers to a Race Directors or Technical Directors judgment or decision.
7. It shall not be possible to protest or appeal technical inspection quipment, scoring or timing equipment.

EJECTION FROM RACE SITE

The Race Director has the right to eject any person(s) from the pit, paddock (staging area) or race track area. CONDUCT OF PARTICIPANT (OFFICIALS, DRIVERS, CREWS, ETC.)

1. Vulgarity, derogatory or offensive language could result in disciplinary action, ejection from race site and be subject to fines and penalties.
2. Any participant that threatens bodily harm or assaults any official, driver, crew, etc., may be subject to disciplinary action, ejection from the race site and be subject to fines and penalties.

NOTE:

If transponders are being implemented in various circuits in place of manual scoring. In circuits where transponders are used, transponders will be mandatory. The following rules will apply to transponders:

1. Transponders must be hard mounted on the center line, between the two clutches on either side of the snowmobile. (It is recommended the transponder be mounted on the muffler side, away from the moving clutch components.)
2. It is the driver's responsibility to ensure a working transponder is in place prior to the start of the race. (In the event there is not a transponder mounted on the sled, the driver will be scored last in that event.)
3. It is the driver's responsibility to ensure the transponders is charged prior to an event. If a driver has a transponder which is not fully charged, they will be required to rent a transponder prior to the event. If a driver participates with a non-charged transponder and the signal strength is too weak to register, the driver will be scored last.

QUALIFYING & ELIMINATIONS

ROUND ROBIN:

A Round Robin will be used for ALL classes. It will consist of two (2) or three (3) rounds where driver entries will be divided into heats. Finish positions will be added together with the low score being the best. Ties will be broken with the last round counting the most and the first round counting the least, then "TIE BREAKERS" come into effect. All drivers who start a round will be given a finish position. Drivers failing to start will be given a DNS and fifteen (15) will be used on that round for the master score sheet.

Technical penalties will result in a last place finish. Disqualification penalties will be given a DQ, and twenty (20) will be used on that round for the master score sheet. If the DQ penalty is issued, no "year end" points will be awarded to the driver.

PLACE HEAT FINAL

1st 10 25

2nd 9 22

3rd 8 20

4th 7 18

5th 6 16

6th 5 15

7th 4 14

8th 3 13

9th 2 12

10th 1 11

11th 1* 10

12th 1* 9

13th 1* 8

14th 1* 7

DQ 0 0

*If WPSA has to run more than ten (10) riders in a heat, all riders scored after 10th will receive one (1) point.

The top ten (10) drivers from the round robin will move into the final, the next ten (10) will race in the LCQ.

TIE BREAKERS

In classes using transponders; ties will be broken by the "fastest race" completed in qualifying for the respective class. When transponders are not

used, Ties will be broken with the last round counting the most and the first round counting the least, then "TIE BREAKERS" come into effect.

Qualifying tie breakers:

1st 3rd Round

2nd 2nd Round

3rd 1st Round

4th Number of drivers faced in rounds.

5th Coin toss

ADVANCING FROM THE "QUALIFIER" (LCQ) [Qualifying & Eliminations]

1. Top five (5) Pros (includes Pro Women and Pro Plus 35) and Semi Pros advance to final in the National events.
2. Top two (2) Pros advance to the final in the Regional events.
3. A "Qualifier" (LCQ) for the Pro Plus 35 and Pro Women will only be used if 20 or more drivers start an event.
4. A Pro Plus 35 or Pro Women class with less than 20 drivers will use qualifying order to determine the back row of a final. The top 10 drivers will start in the front row the next 5 drivers will start in the back row. Provisional starts will be used for row 3 of the final.

PROVISIONAL STARTS

Provisional starts will be used ONLY at National events. Pro and Semi-Pro drivers who are in the top twelve (12) in the points standings going into the event will be allowed a back row start in the Pro and Semi-Pro Last Chance Qualifiers (LCQ). In the Pro Plus 35 and Pro Women classes, the top five (5) will use provisional starts for the back row of the LCQ. In the event there is NO LCQ (less than twenty (20) drivers), the "top five (5)" provisional rule will be used for row three (3) of the final.

ALTERNATES FOR PRO/SEMI-PRO QUALIFIER AND FINAL

1. Alternates can be posted for the Pro/Semi-Pro LCQ and/or the Pro/Semi Pro final. The same qualifying system will be used to determine the alternates as was used for the normal qualifiers.
2. The next available alternate(s) may start the race if one (1) or more of the normal qualifiers fail to start the final. (Alternates may not be used once a race has started, for example a red flag restart)

POINT SYSTEM

1. For the Driver Championship, the points stay with the driver. For the Manufacturer's Championship, the points stay with the snowmobile (National Circuit only).
2. At WPSA National events, Pro drivers will receive ten (10) points for participation at each event.
2. WCIS reserves the right to ask any driver to move up to the next highest class if necessary.
3. No points will be awarded in an LCQ.
4. All events count towards the season championship in their respective series.
5. Points will be kept in the Pro and Semi-Pro classes only at regional events, all classes will use a round robin format and points structure.
6. Pro Women's and Pro Plus 35 classes will not be offered. A schedule will be released prior to the start of the season. All scheduled events will count towards the season point standings.
7. The finish order of an event will be based on the number of laps completed by a driver.
8. It is the responsibility of the driver to verify they have received the correct points for a race. Drivers will have ten (10) business days from the posting of points on the website to file a written protest to WCIS Headquarters regarding the drivers concern. After ten (10) business days, points will be reviewed at the discretion of WCIS.

TIE BREAKERS & END OF SEASON POINTS STANDINGS

- 1st Last event run in series counts the most.
- 2nd Next to the last round back to earlier rounds of series.
- 3rd Number of drivers faced in entire series.
- 4th Number of drivers faced in last round back to first round.
- 5th Coin toss.

DRIVER PAYOUT

Payout is based on the number of driver entries and the added purse money at each event. Payout will generally be for Semi-Pro, Pro Women, Pro Plus 35 and Pro classes only.

1. Added purse money will be in the Pro class.
2. WCIS reserves the right to modify payout schedule for any event.
3. Payouts for the National and WCIS owned regional circuits will be mailed out from WCIS headquarters.

4. Any driver with over \$600 in winnings at the end of the calendar year will be issued a 1099 tax form of the following year for tax purposes.
5. It is the driver's responsibility to know what manufacturers and other sponsors contingency program requirements are and to follow up on all necessary procedures to collect on these programs.
6. Trophies may be available at all WCIS events. The location where you can pick up your trophy will be announced at the drivers meeting.
7. All non-US residents could be subject to US tax laws and withholdings; WCIS reserves the right to withhold taxes per US tax laws).

SNOCROSS TECHNICAL VIOLATIONS

Driver infractions/disqualifications in a Snocross event will be forwarded to all CIS affiliates. Drivers may be disqualified for the following technical violations:

1. Running without a hood or shroud in position.
2. Running with altered numbers.
3. Running with bibs not in position.
4. Receiving unauthorized assistance.
5. The driver, group of drivers or any crew members attempt to harass race officials, in any manner.
6. Course cutting.
7. Failure to stop for Post Race Technical Inspection.
8. Failure to use proper safety equipment.
9. Allowing non registered drivers to operate a driver's machine on the track during a practice lap or during a race.
10. Running without helmet strapped.
11. In the event a driver becomes dislodged from their machine or crashes, and the engine continues to run, the safety disconnect switch fails to function, or is not properly fastened/attached to the driver, while the engine is running, the driver will be disqualified from the heat that the infraction occurred. It is the driver's responsibility to fasten the tether securely.
12. Refueling the machine on the start line.
13. Running while the clutch is exposed.

NOTES

These regulations are comprised of definitions and allowable modification or alterations. If a definition, modification or alteration is not cited then it is to be construed that no modification, alteration or change can be made to the component unless it is specifically approved by the rules committee.

Existing rules may be revised, or new rules may be added after this rulebook was printed. For the latest updates, please check our website.

ALL CLASSES MACHINE REQUIREMENTS

The condition of a machine is the responsibility of the driver. A driver may be disciplined if a driver's machine is modified so as to defraud the officials or other competitors.

SAFETY SWITCH

A functional and operational secondary safety shutoff switch (kill switch) that will terminate ignition is mandatory in all classes. The switch must be located on the right side of the handlebar. The switch may be either the "click-on, click-off" type or the springloaded, push and hold type.

TETHER SWITCH

In the event that a driver becomes dislodged from his or her machine or crashes, and the engine continues to run, and the tether (safety disconnect) switch fails to function or is not properly fastened/attached to the driver while the engine is running, the driver will be disqualified from the heat that the infraction occurred. It is the driver's responsibility to fasten the tether securely. Battery operated electric fuel pumps must be connected to the tether switch. This includes electrically controlled fuel injection systems.

TRACK & TRACTION

1. Regardless of track length or width, a machine is limited to ninety-six (96) sixty (60°) degree unsharpened, unmodified single point picks/studs. Studs must conform to the illustration above.
2. All components of the traction devices must be located in the center of the track between the inside edges of the slide runners (hyfax) and a minimum of 33/4 inches from the edge of the track.
3. No grass hooks or paddles allowed.
4. The stud backing plate maximum size is 2 inches x 21/4 inches. Backing plates must be commercially available.
5. Backing plates may not extend beyond the height of the rib and must rest against the rib. No sharpening (vertically or horizontally) or modification of the backing plate.
6. All studs must be directly aligned with a "leading" rubber lug and no more than 11/4 inches behind the leading lug. The 3/8 inch maximum penetration measurement will be taken off the top of the leading lug. The measurements are taken parallel to the edge of the track and parallel to the flat of the track.

7. Titanium traction products are allowed.
8. Add-on traction devices (including all cleats, studs, screws and paddles) are NOT allowed.
9. Maximum track lug height is 1.75”.

IGNITION & ELECTRICAL

1. All lenses must be taped over with transparent tape (no colored tape).
2. Lighting required for the class must be operational at the start of the race. Light failure during a race is not grounds for disqualification.
3. Wet cell must be enclosed in a non-conductive battery box. The positive terminal must be shielded. The battery box must be securely held in place.

SKI SUSPENSION & STEERING

Maximum ski distance is 43 1/2 inches measured under the spindle. The carbide runner must be centered on the ski board.

SKIS

1. Aftermarket skis are allowed.
Skis must be commercially available.
2. Minimum ski width is 3 1/2 inches. Main keel and ski unner (cutting edge) must be centered on sk board. Main eel maximum depth is 1 1/2 nches without ski runner. ther keel(s) maximum depth s 5/8 inch. No sharp edges re allowed on skis.
3. May reinforce skis on the top side only.
4. Skis and ski loops must conform to the ski rules in the GENERAL ULES AND REGULATIONS ection. Skis and ski loops must be intact at the start of each race. In the nterests of safety, a driver may be black flagged if a ski loop is damaged in such a ay as to cause a hazard. Ski loop leading edges not one (1) inch in width or not eeting the minimum radius rule must be padded.
5. Ski skins are allowed.

SKI RUNNERS

1. Ski Runners must be commercially available.
2. Only one cutting edge is allowed. The minimum cutting angle is sixty (60°) degrees. No grinding or odification of the host bar or cutting edge is allowed.
3. Host bar may be any shape that conforms to the rules.
Except for the cutting edge and groove for affixing cutting material, all eges must have a minimum radius or forty-five degree (45°) chamfer of 1/16 inch (see illustration).

4. Shape of host bar and cutting edge must limit penetration to 3/16 inch. Shoulder required adjacent to cutting edge if host bar is not round or oval. Minimum radius of round or oval host bar adjacent to cutting edge is 7/32 (0.219) inch.
5. Maximum height and width is 5/8 inch. Minimum width adjacent to cutting edge is 3/8 inch for host bar which is not oval or round. Ski runner must fit within 5/8 inch square (see illustration).
6. Rules Committee may determine compliance of a particular product.
7. Non traction events: Carbide ski runners or any ski runners with sharp cutting edges are not allowed. Ski runners must have rounded edges where they contact the arena surface.
8. Ski runners without sharp edges or carbide inserts may be any shape so long as they conform to Snocross maximum and minimum dimensions for ski runners.

FRAME & BODY

1. Dulled foot traction devices are allowed on the running boards.
 - a. On the flat of the running board - traction devices must be dulled and be no higher than 1/2 inch above the flat of the base of the traction device.
 - b. On top of the rolled edge - traction devices must be dulled and be no higher than 1/4 inch above the top of the rolled edge of the running board.
 - c. The traction device may extend a maximum of 1/4 inch beyond the side of the rolled edge for the purpose of mounting. There shall be no sharp edges to side of the rolled edge.
2. Running board extensions are not allowed.
3. The rear snow flap must be in contact with the course surface when driver is seated.
4. The rear snow flap must be held down and restrained from rearward movement.
5. Snow flaps must be restrained by non-elastic material.
6. The rear snow flap must be constructed of a semi-rigid material such as HD polyethylene or UHMV polyethylene.
7. Snow flaps must overlap the widest part of the rear tunnel opening by at least 1 inch on each side.
8. The color orange is not allowed on machines in Snocross racing.

LEGAL FUEL REGULATIONS

1. A contestant appealing a fuel disqualification must bear the expense of the fuel analysis and handling.

2. Only an approved commercially available pump gasoline will be legal. The gasoline may be mixed with petroleum, organic, vegetable, or chemical base lubricants. The use of oils, fuels (including gasohol) and additives providing power boosting characteristics are strictly forbidden.

NOTE: When this rulebook went to print there were ongoing discussions about making changes in the fuel rules. For the latest fuel rules and updates, please check with our inspection Station or check with your circuit's TECH Director prior to the race.

PRE-RACE SAFETY INSPECTION

1. Pre-race safety inspections are mandatory for driver and machines at all races. Pre-race inspections do not certify that the machine is qualified or constituted as legal for class participation. Post-race technical inspections determine machine qualification.
2. All aspects of modification are contingent upon safety inspection by the Technical Director. The Technical Director may remove any machine from competition that does not meet safety requirements.
3. Damaged or broken safety equipment (not including tether switch) not detected during a race is not grounds for disqualification after completion of that race unless the driver is black flagged during the race in question.

SEALS

Drivers will allow the installation of a seal or seals on the engine and/or body of their racing machines. To change the seal, mutilate it or try to break it, or re-use it, during the weekend or event where it is installed without the consent of the Race Director, could result in the responsible driver being called before the disciplinary committee for strict discipline. Accidental breakage of the seal must be reported to the Race Director immediately.

MANDATORY TEARDOWN

1. The Technical Director will select the machines for mandatory teardown and inspection. The machine's driver will be notified at the completion of the race if he/she is to report to teardown.
2. Any driver refusing a teardown will be disqualified.
3. The driver and/or the driver's mechanic will perform the teardown to the point required by the Technical Director.
4. The driver and/or the driver's mechanic will be the only two (2) people allowed.
5. Inspected machines will not be reassembled by the inspection group with the machine in the inspection area.

The sanctioning organization assumes no responsibility for impounded machines.

STOCK SNOWMOBILE REGULATIONS

The machine must have the original OEM engine, hood, intake, exhaust, frame, track, suspension, cowl and drive. Named components must be of the same model and year, or properly filed OEM replacement parts.

FRAME & BODY

1. All chassis will have OEM tags and/or serial numbers affixed to the frame.
2. Reinforcing, by welding and/or bracing will be allowed.
3. Removal of any material from total machine by means of heat, acid, drilling, grinding, sand blasting, peening, substitution or total elimination will not be allowed.
4. Access openings will be allowed for component removal or service but closures must be made of original type materials. Vents/scoops must be OEM for the model. Vents may be covered or closed. No additional vents or scoops may be added. Crankcase and/or brake cooling ducts must remain within the confines of the sled and only use an existing vent.
5. Hoods may not be removed.
6. Windshields must be OEM or equal to an OEM windshield in dimension and be mounted in OEM location as filed. Minimum stock windshield height must be maintained and must have a safety edging. The windshield may be altered for handlebar movement. The windshield must be intact at the start of each race day. Modified / Open machines do not have to have windshields.
7. The seat must remain OEM for the model. Padding may be added or subtracted to improve driver comfort and safety. Seats may be lowered but must be at least five (5) inches thick at its minimum dimension. Height will be measured from top of original tunnel to top of seat in rider less state. The seat must be upholstered. The seat may not be moved forward, backward, or sideways of the OEM location.
8. Insulation may not be removed.
9. Skid plates may be added for protection of sled bottoms. Skid plates must be securely fastened.
10. Additional plate material may be added to the tunnel at the suspension mounting holes.
11. It is highly recommended that the sides of the rear tunnel opening be enclosed with comparable tunnel material. The tunnel covering is required to keep a ski or driver's extremities from entering the tunnel area.

12. Tunnel protective wear strips may be added, removed or altered. Liquid spray coating is allowed.
13. Bumpers may be added, removed or relocated and not be a safety hazard.
14. Fuel tank must be OEM as supplied with the machine or opaque (translucent) as supplied by the OEM manufacturer. The translucent tank must be of equal dimensions and capacity to that supplied by the original OEM manufacturer. An OEM fuel tank is the only tank that can be used to supply fuel to the engine.
15. Fuel lines must be free of obstructions by other machine components.

ENGINE

1. All engines will have an OEM tag and/or serial numbers affixed to the engine.
2. No component of the engine may be altered, changed or enlarged from the engine manufacturer's original stock specifications, nor may any additional components be added to the engine. Blueprinting will not be allowed. No removal of material whatsoever will be allowed. This is to include polishing, port matching, deburring, glass or sand blasting surfaces or material removal for the purposes of engine balancing or other reasons.
3. Maximum cylinder overbore for wear or cylinder repair cannot exceed .020 inch (0.50mm).
4. Stock OEM for the model pistons only are allowed for replacement.
5. There will be no more than one (1) cylinder base gasket to a cylinder. No changes in the engine dimensions can be made by gasket adjustments.
6. Rotary valve timing/duration must remain as filed by the manufacturer.
7. OEM carburetor slide valves and replacement jet options will be allowed without modification.
8. An adequate return spring on the throttle is required.
9. Choke mounting location may be moved for the driver's comfort. The choke system may be disconnected.
10. No pressure charging is allowed.
11. The engine air intake system is to include any: cowl vents, airbox, noise reducing foam (cowl vents & air box), carb boots, carburetors, clamps, rotary valves, reed valves, carburetor flanges and oil injection nozzles that are original OEM equipment for that make and model. No changes or modification will be allowed to any part of the engine air intake system or mounting location.
12. Deep snow cover/foam must remain in place.
13. The engine must remain in the original mounting location.
14. No pressurization of fuel tanks or lines is allowed.

15. Fuel lines must be free of obstructions by other machine components.
16. No additional engine cooling systems are allowed.
17. If oil injection is OEM standard, oil injection system and all associated components must be installed in their OEM configuration, but may be disconnected. Oil injection nozzles may be removed or plugged. Premixed oil and fuel may be used.
18. Spark plugs do not have to be OEM.
19. The exhaust system is to include any header flange or pipe, Y pipe, expansion chamber, pulse charger, muffler and tail pipe that are original OEM equipment for that make and model.
20. No changes or modifications will be allowed to any part of the exhaust system or mounting locations.

DRIVE

1. Machines must have the original OEM variable speed converters supplied by the manufacturer for that make and model or a part that has superseded the original OEM part for the model. Factory designated replacements must be submitted to the Race Rules Committee for approval and implementation.
2. Any springs, weights or ramps may be used. No clutch engagement RPM limit.
3. No machining on clutches to accommodate springs and weights are allowed.
4. In the primary clutch, metal may be removed but not added to ramps or flyweights.
5. Secondary clutch cams may be cut to any angle. Billet helixes are allowed.
6. No overdrive machining.
7. Drive belts do not have to be OEM.
8. Any drive chain and sprockets may be used.
9. Chain case must be original OEM for the model equipment and must remain in the original mounting location. The chain tensioner may be changed to any OEM equipment.
10. Track drive axle and sprockets must be OEM for the model. Sprocket diameter may be trued round.
11. Brakes may be changed or altered, but must be operational at all times. No dual brakes are allowed. Brake components must be commercially available. If brake disk system is relocated, the stock brake disc must remain in place. Liquid cooled systems allowed Brake disk may not be drilled or slotted. OEM diameter and thickness must be maintained. The brake

material may not be substituted with any other material. Aluminum and/or carbon brake disks are not allowed.

12. The brake control handle must remain in OEM location on the left, rear side of the handlebar.

13. Existing vents may be used to direct cooling air to the brake components. The brake disk shall not extend outside of the bodywork.

SKI SUSPENSION & STEERING

1. A maximum sled/chassis width will be 43 1/2 inches measured from one ski carbide cutting edge to the opposite ski carbide edge.

2. No substitution of material is allowed on front suspension and must remain in original mounting location in both bulkhead and spindle housing.

3. Machines must remain stock width.

4. Sway bar may not be relocated. Sway bars must be OEM for the model, or another sway bar from another stock qualified model within the brand. Sway bar may be disconnected or removed. If disconnected and not removed, all remaining components must be secured so as not to endanger the driver or other drivers.

5. Limiting devices of any length may be used. A minimum of two (2) inches travel, measured from the lowest part of the belly pan to flat ground surface with the driver on the sled, must be maintained.

6. Reinforcement of components will be allowed by welding or bracing. Structural integrity must be maintained.

7. Spindles may not be shortened.

8. Any spring may be used on the suspension and may be shortened or heated.

9. Any shock absorber, fluid, gas (non-flammable), or fluid metering valves may be used and may be shortened. OEM length for the model must not be exceeded.

10. Handlebars must be intact at the start of each race day. Any commercially available handlebars are allowed and may be altered to fit the driver. Open ends must be capped. Handlebars must be padded. Column or post must remain in its OEM position. Grips and controls may be modified. The throttle will be operated with a thumb mechanism located on the handlebar to the rear of the machine (no twist grips).

SKIS & SKI RUNNERS

1. Aftermarket skis are allowed. Skis must be commercially available. Ski, ski loop and ski runner must conform to General Rules and Regulations.

2. Skis may not be interchanged between brands.

3. May reinforce skis on the top side only.
4. A maximum ten (10) inch turning material per ski is allowed. The turning material must be continuous. Any ski edge with more than 1/2 inch turndown is considered a cutting edge.
5. Ski skins are allowed.

TRACK SUSPENSION

1. Suspension must be OEM for the make and model. Suspensions must remain in the original mounting location, or optional locations pre-drilled in backing plate by the manufacturer. Suspension components must remain in original location or optional locations filled by the manufacturer. No substitution of material is allowed.

2. Rails may not be bent or shortened.

3. Rear idler and marginal snow wheels may be added or removed, along with mounting brackets for an OEM wheel kit. The wheel diameters may be trued round.

4. Slide rail lubrication will not be allowed.

5. Any hyfax is allowed.

6. Any shock absorber fluid, non-flammable gas, or fluid metering valves may be used.

The shock may be shortened, OEM length for the model must not be exceeded.

7. Any springs are allowed. The springs may be removed and replaced with some other type of cushion device.

8. Springs may be shortened or heated.

9. Suspension may be reinforced but not re-engineered.

TRACK & TRACTION

1. The length and width of OEM track shall be as produced by the manufacturer.

2. The track must be OEM for the model or a designated and approved optional track specifically for the model. (OEM may designate up to one optional track per model. Aftermarket molders of tracks may designate up to one (1) track per snowmobile brand. A list of designated and approved optional tracks will be published by ISR). Any approved track that is not commercially available to the driver (not in inventory) within 5 days will be banned from racing.

3. In the 440 Stock Class snowmobiles that are 2005 models or newer must use the OEM for the model track. Older models comply with rule number 2 (above).

4. Identification numbers affixed or molded into tracks by the molder must remain completely visible and unmodified. No traction device or other item may be installed over the identification numbers on the track. Identification numbers include model number, serial number and/or any other information applied to the track by the molder.
5. Configuration of the track, including length and width, must allow for installation without modification to the track, frame, tunnel, suspension or drive components.
6. The track must remain as manufactured. No trimming or shaving of the track grouser bars, rubber studs/snow lugs will be allowed. Any approved track that is not commercially available to the driver (not in inventory) within five (5) days will be banned from racing.
7. No cleats or partial cleats may be added.
8. Grouser bars and rubber snow lugs must remain OEM height and width.
9. Any commercially available guide/track clips may be used. No traction devices may be added to track clips.
10. Tracks may not be reversed.
11. Studs cannot be more than 3/8 inch above the highest point of the track.

IGNITION & ELECTRICAL

1. All machines must be equipped with a safety disconnection (tether) and be operable at all times. This will be the responsibility of the driver. Tethers must be used and attached to the operator whenever the engine is running, this includes pit areas, staging and the race course.
2. The maximum tether cord length will be five (5) feet. Verification of tether cord length will be determined at tether cords fully extended length.
3. The tether cord will be securely fastened to the driver. No alligator clips are allowed.
4. The tether switch will be securely mounted in a location on the machine other than on the handlebars.
5. A functional and operational secondary safety shutoff switch (kill switch) that will terminate ignition is mandatory in all classes. The switch must be located on the right side of the handlebar.
6. Wiring may be removed.
7. Instrumentation may be added but must not provide a safety hazard. Instrumentation may be disconnected but not be removed.
8. Head, tail and brake lights must be original OEM equipment. They must be taped over with transparent clear tape and must remain in original mounting location.
Must be operational at the start of the race. Light failure during a race is not

grounds for disqualification. The tail light cannot be battery operated.

9. Ignition must be OEM for the year and model.

10. CDI/ECU module may be reprogrammed.

11. Fixed ignitions may be moved (+ or -) four (4) degrees.

12. No aftermarket device allowed which interrupts ignition for the purpose of launch control or traction control unless OEM for the model.

13. Battery operated electric fuel pumps must be connected to the tether switch. This includes electrically controlled fuel injection systems.

14. Wet cell must be enclosed in a non-conductive battery box. The positive terminal must be shielded. The battery box must be securely held in place.

MODIFIED / OPEN REGULATIONS GENERAL RULES

1. Maximum displacement 600cc.

2. All machines must meet the safety guidelines.

3. All competing machines may be individually inspected by race officials for safety and structural soundness.

4. All machines must be equipped with a tethered safety kill switch which will stop the motor and any electric fuel pumps being used. The tether cord must be securely attached to the operator at any time the motor is running.

5. The minimum weight of the machine (as raced) shall be four hundred and thirty (430) lbs.

FRAME & BODY

1. 600cc maximum

2. Normally aspirated.

3. No nitrous oxide systems.

4. All machines must have a hood, belly pan, contoured seat and an enclosed tunnel.

Windshields are not mandatory.

5. Chains, pulleys and exposed moving parts will be isolated from the driver and other

competitors by a shield capable of retaining all accidental explosions and component

impacts. The integrity of protective shields shall be at the Tech Director discretion.

No holes may be drilled in protective shields.

ENGINE

A functionally silenced exhaust system is required.

DRIVE

1. Any clutch system is allowed.

2. If stock clutches are used, clutch cover equivalent to stock or better is allowed.
3. For all others, the clutch cover must be separate from cowl configuration and cover clutches to center of bolt or below. Clutch cover guards must be .090 inch 6061 T6 aluminum or equivalent steel material (other materials not allowed) and be covered with six (6) inch belting. If clutch cover is constructed of .125 inch aluminum, belting is recommended, not required. Machines with removable side panels may bolt clutch cover guards to side panel to meet this requirement.
4. On machines which comply, in all respects, with the stock class rule, the stock belt guard may be used when moving up to an Open class.

SKI SUSPENSION & STEERING

1. Maximum carbide distance cannot exceed 4 3/2 inches measured under the spindle.
Carbides must be centered on the ski board.
2. Turing carbide length is unlimited.
3. The handlebar ends must be capped.
4. Handlebars must be padded.

TRACK & TRACTION

1. Track must be one piece molded and commercially available.
2. There is no minimum track width.
3. No track holes larger than 7mm.
4. Traction lugs may be trimmed to within 1/4 inch of track rods and fabric.
If any lugs in the center portion of the track are trimmed, no traction products are allowed on the track. If outer band lugs are trimmed off at a forty-five degree (45°) angle, track studs may be used according to traction rules.
5. Stud ruling is the same as stock classes.

IGNITION & ELECTRICAL

Taillight assembly must be from a stock qualified machine. Running lights and brake lights are required.

CONTROLS

1. Brakes shall be operative at all times. The brake lever must be located on the left side of the handlebar.
2. Throttle controls are the same as stock class.

NOTES

Multiple Violations of the same rule may result in suspension or disqualification.

These regulations are comprised of definitions and allowable modification or alterations. If a definition, modification or alteration is not cited then it is to be construed that no modification, alteration or change can be made to the component unless it is specifically approved by the rules committee.

Existing rules may be revised, or new rules may be added after this rulebook was printed. For the latest updates, please check the website at www.wsaracing.com.

JUNIOR 10 - 13

The Junior 10 - 13 class is available to drivers age 10 - 13. Only designated Fan models, 600cc or less, are eligible for competition.

1. A Junior 10-13 racer cannot advance to Junior 14-15 racing until his/her 14th birthday.
2. 10-13 year old drivers who start in one circuit in the 10-13 year old class and then turn 14, may continue to run in the 10-13 year old class in that circuit. However, that is the ONLY class they can run in that circuit. If, after turning 14, they race in another circuit, they must race in the 14-15 year old class in the second circuit.
3. 10-13 year olds may NOT race in any class other than their 10-13 year old class. Any drivers caught trying to run other classes may be suspended from racing any WPSA

sanctioned events for one full year.

GENERAL COMPETITION & SAFETY RULES

1. If it isn't stated in this book that it can be done, consider that it cannot be done.
2. All machines must comply with the General Requirements section as specified.
3. All machines must have the original OEM (or factory designated replacement) engine, hood, track, frame, cowl, gas tank, carburetion, air box, suspension and variable speed converter supplied by the manufacturer for that particular model.
4. Factory supplied options are not allowed.
5. Engine kits are allowed.

FRAME & BODY [Junior 10 - 13]

1. OEM windshields for the model or factory options are allowed. The windshield may be altered for the driver's safety and comfort, but must extend five (5) inches above the highest point of the hood. If the original OEM windshield for the model is lower than five (5) inches it may be used. Windshield must have safety edging.
2. Windshields must be intact at the start of the race.
3. Windshield must remain in OEM mounting location.
4. Removal of stock air vent gills including intake or exhaust are not allowed.
5. No additional venting is allowed.
6. Protective taping or screening will be restricted to the external opening only.
7. Seat and fuel tank must remain OEM for the model (seat color optional)
8. The OEM fuel tank is the only tank that can be used for fuel. The lubrication tank cannot be used as a fuel tank.

ENGINE

1. No component of the engine may be altered, changed, reduced or enlarged from the

engine manufacturer's original stock specifications, nor may any additional components be added to the engine.

2. Maximum cylinder overbore for wear cannot exceed .020 inches (1/2mm).

3. Replacement pistons must be stock OEM for the model.

4. Blueprinting of engines is not allowed. No removal of material will be allowed. This

is to include polishing, port matching, deburring, glass or sand blasting surfaces or

material removal for the purpose of engine balancing or other reasons.

5. There will be no more than one (1) cylinder base gasket to a cylinder. No changes in

engine dimensions can be made by gasket adjustments.

6. A maximum of one (1) venturi per cylinder will be allowed.

7. OEM carburetor slide valves and replacement jet components without modification

will be allowed in all stock classes. No modification to carburetor body will be

allowed.

8. Engine must retain its original cooling concept (fan or free air cooling circuits cannot

be modified or removed, except for quick disconnects.)

9. The oil injection pump must remain in place and functional. Lines may be removed

and plugged, premix gasoline may be used.

10. The OEM exhaust system for the model must be furnished complete on the

machine. The exhaust system must be fully contained within the confines of the

cowl or the chassis and the direct exhaust emissions pipe must not protrude more

than three (3) inches beyond the chassis or hood.

11. Spark plugs do not necessarily have to be OEM equipment.

12. No additional fuel pumps may be added to the stock carburetors.

13. The throttle may be changed but must be thumb operated with a direct mechanical

operated mechanism.

DRIVE These components will be interchangeable between any brands providing there is no modification to the clutch required to make these components fit.

1. Any combination of factory springs, weights, ramps, etc. may be used.

Clutch

engagement speed shall not exceed 6000 RPM when machine movement is initiated

for V-bell torque converter drive systems.

2. In the primary clutch, metal may be removed but not added to ramps or flyweights.

3. Cams may be machined for angle change. No material may be added. No welding will be allowed (billet helixes allowed).

4. Drive belts do not have to be OEM.

5. Any drive chain or sprocket may be used.

6. Brakes must remain OEM for the model and year.

7. The brake lever may be modified or changed to fit the driver but must remain hand

operated with a direct mechanical operated mechanism. The function of the brake

system may not be compromised. The brake lever must not extend beyond the end

of the handlebar.

SKI SUSPENSION & STEERING [Junior 10 - 13]

1. Any properly filed OEM spring allowed (+ or -) 1/2 inch (12.5mm) overall length.

2. Limiter strap allowed to limit travel, but must maintain two (2) inches of travel (no locked suspensions).

3. No device may be added that stops the suspension from functioning (no locked suspensions).

4. Any commercially available handle bar is allowed. Handle bar extensions will be legal. All ends must be plugged.

5. Any shock absorber, fluid, gas (non flammable), or fluid metering valves may be used.

6. Torsion bars are not allowed.

SKIS & SKI RUNNERS [Junior 10 - 13]

1. Aftermarket skis are allowed. Skis must be commercially available.
2. Must conform to the General Requirements, Skis & Ski Runners section.
3. May reinforce skis on the top side only.

4. Skis and ski loops must conform to the ski rules in the GENERAL RULES AND REGULATIONS

section. Skis and ski loops must be intact at the start of each race. In the interest of safety, a driver may be black flagged if a ski loop is damaged in such

away as to cause a hazard. Ski loop leading edges not one (1) inch in width or not

meeting the minimum radius rule must be padded.

5. Ski skins are allowed.

TRACK SUSPENSION [Junior 10 - 13]

1. Suspension must be OEM for the make and model. Must remain in original mounting location or optional locations pre-drilled in backing plate by the manufacturer.

Suspension components must remain in original location or optional locations filed by the manufacturer. No substitution of material allowed.

page :: 32 2005 - 2006 WPSA RULES AND REGULATIONS

2. Rails may not be bent or shortened.
3. Rear idler and marginal snow wheels may be added or removed along with mounting brackets from an OEM wheel kit. Wheel diameters may be trued round.
4. Slide rail lubrication will not be allowed.
5. Any hyfax is allowed.
6. Any shock absorber, fluid, gas (non-flammable), or fluid metering valves may be used. May be shortened, but OEM length for the model must not be exceeded.
7. Any spring is allowed. Must maintain design concept (i.e. torsion or coil spring).
8. Springs may be shortened or heated.

TRACK & TRACTION [Junior 10 - 13]

1. Track may not be reversed.
2. OEM track guide clips may be added.

IGNITION & ELECTRICAL [Junior 10 - 13]

1. Head, tail and brake lights must be original OEM equipment and must remain in the

original mounting location. They must be operational at the start of a race.

Light

failure during a race is not grounds for disqualification. Tail lights cannot be battery operated.

2. Glass lenses must be taped and remain in place.

3. Stock machines will be allowed to add or remove tachometers, speedometers or

heat gauges, however, the openings must be closed.

4. Spark plugs, spark plug wires and connectors do not have to be OEM.

5. The cooling system must remain in the OEM location except that tunnel mounted

heat exchangers may be relocated for stud clearance, but must remain within the

confines of the tunnel.

MATERIAL REMOVAL [Junior 10 - 13]

Removal of any material from total machine by means of heat, acid, drilling, grinding,

sand blasting, peening, substitution or total elimination will not be allowed unless otherwise

specified in this section.

page :: 33 2005 - 2006 WPSA RULES AND REGULATIONS

NOTES

120 / 4-STROKE RACING

The intent of these rules is to establish a venue in which all qualified drivers and

machines can compete at their own level. These rules are definitions and guidelines for

allowable modifications or alterations. If a definition, modification or alteration is not

cited, then it is to be construed that no modification, alteration or change can be made to

the component unless it is specifically approved by the rules committee.

These rules are guidelines, all competitors **MUST** check with the every circuit prior to

racing as rules may vary slightly within each region.

ELIGIBLE DRIVERS

Age 4-12 for stock class

Age 6-12 for Champ

ELIGIBLE SNOWMOBILES

Arctic Cat Z 120

Ski-Doo Mini Z

Polaris XCR 120

120/4 STROKE CLASSES [120 / 4-Stroke Rules]

Novice Stock – For beginner drivers. A rider will no longer be allowed to race once

he or she has 3 first place victories.

Stock – Stock Machines ONLY. You may change gear ratio to a 420 ratio, 10 tooth

and 42 tooth will be allowed. Must follow ISR Stock Rules (included).

Improved Stock – Must follow ISR Stock Rules (included).

Champ 120 – Must follow ISR Stock Rules (included) with the exception of Rock

Maple Racing amended rule change.

(Classes may vary from region to region).

GENERAL SNOWMOBILE RULES [120 / 4-Stroke Rules]

All 120/4 Stroke Classes are stock based classes. In stock based classes, no change or

modification can be done to the stock qualified snowmobile unless specially allowed by

these rules. If these rules do not specifically allow a change or modification, then it must

be assumed that the change or modification is not allowed.

1. (Snocross and Grass Oval) No traction products allowed.

2. Left side of handlebar may be straightened. Structural integrity must be maintained.

3. An extension may be added to the left handlebar. Maximum 3 inches wider,

maximum 4 inches down. End must be capped.

4. All metal ski hoops must be padded.

IGNITION & ELECTRICAL [120 / 4-Stroke Rules]

Ignition system must be OEM for model. Flywheel can be lightened.

Lighting coil may

be removed. Any commercially available flywheel may be used.

GENERAL COMPETITION & SAFETY RULES [120 / 4-Stroke Racing]

1. Driver entry into an event is open to any qualified individual. The sanctioning body

has the authority to evaluate all drivers to determine their qualifications.

2. Both the owner and driver are responsible to ensure that their snowmobile and

page :: 34 2005 - 2006 WPSA RULES AND REGULATIONS

driver safety equipment conform to all of the rules for the class in which they have

entered. Any driver that does not meet the requirements listed will be subject to

disqualification and forfeiture of any prizes or awards, plus eligibility for the next

two (2) races.

3. Teardown will be at the discretion of the 120 Tech Director.

4. If it isn't stated in this section that it can be done, consider that it cannot be done.

5. The Race Director and/or Tech Director have the authority to determine structural integrity.

6. While driver is on the course, radio communication between driver and crew is not allowed.

MANDATORY DRIVER SAFETY EQUIPMENT [120 / 4-Stroke Rules]

1. Helmet

2. Eye Protection, either a shield or goggles.

3. Shin Guards and Knee Pads

4. Tek-Vest (Upper body protection)

5. Above ankle Boots

6. Mouth guard

STOCK CLASS 120 / 4-STROKE RULES

1. The snowmobile must have original OEM (or factory designated replacement)

engine, hood, track, frame, cowl, gas tank, carburetion, air box, suspension and

clutch supplies by manufacturer for the particular model. Factory designated replacements allowed.

2. Engine RPM and vehicle speed may be monitored at the discretion of the Race

Director.

ENGINE [Stock Class 120 / 4-Stroke Rules]

1. All governor parts must be intact, in place, and functional. Any governor spring

may be used.

2. No component of the engine (including head, valves, cam, and valve springs) may

be altered, changed, or enlarged from the engine manufacturer's original stock specifications

nor may any additional components be added to the engine.

3. Blueprinting of engines is not allowed. No removal of material whatsoever will be

allowed. This is to include polishing, port matching, deburring, glass or sand blasting surfaces or material removal for the purpose of engine balancing or other

reasons.

4. There will be no more than one cylinder base gasket to a cylinder. No changes in

engine dimensions can be made by gasket adjustments.

5. Spark plugs do not necessarily have to be OEM stock.

6. No carburetor/air silencer changes allowed.

7. Jetting changes are allowed.

8. Remote adjustable main jet system allowed.

9. The OEM exhaust system for the model must be used in its entirety. The exhaust

system must be fully contained within the confines of the cowl or the chassis and

direct exhaust emissions from the enclosed area. Muffler components and/or silencing material must be intact at all times.

DRIVE [Stock Class 120 / 4-Stroke Rules]

1. Brake must be functional and operational at all times

2. OEM drive clutch must be used with no modifications.

3. Stock drive clutch engagement must be maintained.

4. No belt drives allowed

5. Chain guard must be in place.

page :: 35 2005 - 2006 WPSA RULES AND REGULATIONS

(Continued on page 36)

6. OEM gear ratio must be maintained.

7. Sprocket ratio changes may be required by circuits in order to equalize performance

between the various models.

SKI SUSPENSION & STEERING [Stock Class 120 / 4-Stroke Rules]

1. Front suspension must be OEM stock.

2. Front suspension must remain in its stock location.

3. Ski widening devices and/or height adjustment devices are not allowed in Stock

classes unless furnished as OEM and properly filed.

4. Suspension travel may be limited by means of limit straps only. Minimal suspension

travel must be maintained. No rigid suspensions allowed.

SKIS & SKI RUNNERS [Stock Class 120 / 4-Stroke Rules]

1. Ski must be OEM for the model and year or a commercially available aftermarket ski

with a minimum overall length of 20 inches.

2. Ski suspension components must be OEM.

3. Ski tips must have ski loops. Steel ski loops must be padded.

TRACK SUSPENSION [Stock Class 120 / 4-Stroke Rules]

1. The complete suspension must be used as furnished and filed by the manufacturer.

2. Commercially available marginal snow wheels may be added to the slide rails.

(Rear axle idler wheels must remain OEM for the model).

3. Suspension travel may be limited by means of limit straps only. Minimal suspension

travel must be maintained. No rigid suspensions allowed.

TRACK & TRACTION [Stock Class 120 / 4-Stroke Rules]

1. The track must be OEM for the model.

FRAME & BODY [Stock Class 120 / 4-Stroke Rules]

1. OEM hoods only. OEM hood may be painted any color.

2. Windshield may be trimmed. Exposed edges of windshield must have safety bead.

3. Front and rear bumpers must be padded.

4. All sharp edges must be padded.

IGNITION & ELECTRICAL [Stock Class 120 / 4-Stroke Rules]

1. An ignition tether switch must be installed and functional.

2. Headlight and taillight must be OEM for the model and taillight must be functional.

page :: 36 2005 - 2006 WPSA RULES AND REGULATIONS

CHAMP 120 CLASS / 4-STROKE

GENERAL REGULATIONS [Champ 120 Class / 4-Stroke]

1. Snowmobile must be an ISR designated 120/4 stroke model that complies with the

General Rules and Regulations section.

2. Engine, frame, hood, and slide rails must be OEM for the model.

ENGINE [Champ 120 Class / 4-Stroke]

1. Must start with OEM filed 120/4 stroke engine.

2. Engine components allowed for modification for change from OEM.

- a. Cam shaft – maximum .290 inch lift
 - b. Valves and seats
 - i. Maximum intake valve diameter 25.2mm
 - ii. Maximum exhaust valve diameter 5.5mm
 - c. Valve springs and retainers
 - d. Tappets and push rods
 - e. Governors may be removed
3. Engine overbore may not exceed .020” (.50mm) of standard bore size for the model.
 4. Engine stroke must be stock as manufacturer’s filed specifications.
 5. Engine components allowed to be modified but must begin as OEM for the engine model.
 - a. Bearings
 - b. Connecting rod
 - c. Piston
 - d. Rings
 - e. Gaskets

DRIVE [Champ 120 Class / 4-Stroke]

1. Clutching is open. CVT type transmission allowed. Drive components must be commercially available.
2. A metal clutch / chain cover must be in place at all times during operation. It must cover clutches, gears, belts, chains, starter cups, and any other rotating components.
3. Brakes must be properly operable at all times.
4. Track drive sprockets may be modified or changed.

SKI SUSPENSION & STEERING [Champ 120 Class / 4-Stroke]

1. Suspension must maintain OEM concept (i.e. trailing arm, “A” arm, etc.)
Ski suspension and steering may be changed or modified. Materials and components must meet or exceed OEM strength and structural integrity. Must maintain suspension travel with driver seated. No rigid suspensions.
2. The structural integrity of the steering and suspension systems must be maintained.
3. Maximum ski stance is 34 inches (measured between ski runner cutter edges).

SKI AND SKI RUNNER

1. Skis may be changed to commercially available aftermarket skis.
 - a. Minimum length for Snocross is 20 in.
 - b. Ski loop must conform to GENERAL RULES AND REGULATIONS.
2. Ski runners must meet competition and safety requirements for snocross racing.

TRACK SUSPENSION [Modified 120 Class / 4-Stroke]

1. OEM track suspension must be maintained, but may be modified.

Material and

components must meet or exceed OEM strength and suspension structural integrity.

2. Suspension may be relocated in frame and suspension travel may be limited with limit straps.

page :: 37 2005 - 2006 WPSA RULES AND REGULATIONS

(Continued on page 38)

3. Must maintain suspension travel with driver seated. No rigid suspensions.
4. Wheel may be added or removed.

TRACK & TRACTION [Modified 120 Class / 4-Stroke]

1. Track must be OEM for a 120/4 stroke model from any snowmobile manufacturer.
2. Track may not be reversed.

FRAME & BODY [Champ 120 Class / 4-Stroke]

1. Snowmobile length must not exceed OEM for the model length by more than 2

inches (ski loop to rear of tunnel)

2. Overall body width must be within 2 inches of OEM for the model body width.

3. Bumpers must be padded (no sharp edges exposed)

4. Snow Flap must be in contact with the course surface when driver is seated.

5. Belly pan required.

6. Bulkhead may be modified or replaced; it must remain within 1 inch of the length

and 1 inch of the width of the OEM bulkhead.

7. Motor MUST stay stock. Gear Change and Jetting will be allowed.

These regulations are comprised of definitions and allowable modification or alterations.

If a definition, modification or alteration is not cited then it is to be construed

that no modification, alteration or change can be made to the component unless it is specifically approved by the rules committee. Existing rules may be revised, or new rules may be added after this rulebook was printed. For the latest updates, please check the website at www.wsaracing.com.

page :: 38 2005 - 2006 WPSA RULES AND REGULATIONS
NOTES

World Powersports Association Headquarters

1863 Buerkle Road

White Bear Lake, MN 55110

Phone: 651-209-7400

Fax: 651-209-7447

General info e-mail: info@wsaracing.com

Rules e-mail: tech@wsaracing.com

Website: www.wsaracing.com

Northwoods Challenge (NWC)

N. WI./Up. MI

Laddy Hlavacek

329 County Road F

Phillips, WI 54555

Phone: 715-339-4207

Fax: 715-339-4207

E-mail: laddy@pctcnet.net

Website: www.northwoodschallenge.com

MN State Championship

MN Snocross

1863 Buerkle Road

White Bear Lake, MN 55110

Phone: 651-209-7400

Fax: 651-209-7447

E-mail: info@wsaracing.com

Website: www.wsaracing.com

Rock Maple Racing [RMR]

E. NY / VT / NH / ME Snocross/Hillcross®

Chuck Minasalli, Beth Walling

18 Coldbrook Road

Wilmington, VT 05363

Phone: 802-464-0427

Fax: 802-464-7626
E-mail: info@rockmaple.com
Website: www.rockmaple.com
Western Snowmobile Racing [WSR]
WA / OR / CA / NV Snocross/Hillcross®
Neil Gardner
P.O. Box 948
Diamond Springs, CA 95619
Phone: 530-622-8304
Fax: 530-622-8530
E-mail: info@wsrracing.com
Website: www.wsrracing.com
WI State Chamionship
WI / N. IL Snocross
1863 Buerkle Road
White Bear Lake, MN 55110
Phone: 651-209-7400
Fax: 651-209-7447 fax
E-mail: info@wsaracing.com
Website: www.wsaracing.com
Woody's WPSA MI Regional Snocross
MI Snocross
1863 Buerkle Road
White Bear Lake, MN 55110
Phone: 651-209-7400
Fax: 651-209-7447
E-mail: info@wsaracing.com
Website: www.wsaracing.com /
www.snowcross.net
WPSA Watercross
MN / WI / IL / MI
Arlen Peterson
207 1st Ave. S.
Frederic, WI 54837
Phone: 715-327-8791
Fax: 715-327-5738
e-mail: info@iwausa.org
Website: www.iwausa.org
Xtreme Ice and Midwest Hillcross®
MN / WI / U. P. MI

Wally & Jean Scheer

3725 Evergreen Lane

Plymouth, MN 55441

Phone: 763-559-7206

Fax: 763-559-7315

E-mail: info@pro-ice.com

Website: www.pro-ice.com

page :: 39 2005 - 2006 WPSA RULES AND REGULATIONS

WPSA Circuit Contact Information

WPSA

1863 Buerkle Rd

White Bear Lake, MN 55110

651.209.7400

www.wsaracing.com